

Applications

Agriculture
Construction and Demolition
Forestry

Lifting and Handling
Road work, Recycling and Cleaning

Main features

Continuous 360° Rotation: Allows the operator to rotate the grapple for perfect alignment or placement.

Two auxiliary hydraulic circuits on the excavator provide the ability to independently control the rotation and grapple open/close functions.

Compatibility

Description	Item number	Compatible with excavator
Demolition & Sorting Grab DGX50.4 - Klac™ System E	7171722.K	E57W (EU only)
Demolition & Sorting Grab DGX50.4 - Pin-On	7171722.P	E62, E57W (EU only)
Demolition & Sorting Grab DGX50.4 - SW03	7171722.L	E62, E57W (EU only)
Demolition & Sorting Grab DGX60.5 - Klac™ System F	7171723.K	E62, E85 (EU only)
Demolition & Sorting Grab DGX60.5 - Pin-On	7171723.P	E85 (EU only)
Demolition & Sorting Grab DGX60.5 - SW08	7171723.L	E85 (EU only)

Weights and Dimensions

Description	Item number	Operating weight (kg)	Shipping weight (kg)	Overall Length (A) (mm)	Overall Width (B) (mm)	Overall Height (C) (mm)
Demolition & Sorting Grab DGX50.4 - Klac™ System E	7171722.K	295.0	295.0	-	500.0	-
Demolition & Sorting Grab DGX50.4 - Pin-On	7171722.P	295.0	295.0	-	500.0	-
Demolition & Sorting Grab DGX50.4 - SW03	7171722.L	295.0	295.0	-	500.0	-
Demolition & Sorting Grab DGX60.5 - Klac™ System F	7171723.K	360.0	360.0	-	600.0	-
Demolition & Sorting Grab DGX60.5 - Pin-On	7171723.P	360.0	360.0	-	-	-
Demolition & Sorting Grab DGX60.5 - SW08	7171723.L	360.0	360.0	-	600.0	-