

Applications

 Forestry
 Agriculture

Landscaping

Main features

 High-torque, low-speed motor increases efficiency while decreasing stalling
 Manual 3-position boom angle
 Left side discharge

 Steel deflector shields protect operator and loader from flying debris
 Cut slightly below ground level to minimize stumps
 It has the ability to cut beyond mounting frame of saw when angled to left

Compatibility

Description	Item number	Compatible with loader
Brush Saw 75	7121030	T110-B, A770-B, T450E IIIB, T590E IIIB, T590B iT4, T650E iT4, T650B iT4, T770E IV, T770E T3, T770B T3, T870E IV, T870B T3, S100E, S450E IIIA, S450B T2, S510E IIIA, S510B, S530E IIIA, S530B, S550E IIIB, S550B iT4, S570B iT4, S590E IIIB, S590B iT4, S630E iT4, S630B iT4, S650E iT4, S650B iT4, S770E IV, S770E T3, S770B T3, S850E IV, S850E T3, S850B T3, A770E IV, S450 V, S510E V, S530E V, T590E V, T450E V, S66, S76, T66, T76, S510B, S530B, S550E V, S590E V, S630B iT4, S650B iT4

Weights and dimensions

Description	Item number	Operating weight (kg)	Shipping weight (kg)	Overall length (A) (mm)	Overall width (B) (mm)	Overall height (C) (mm)
Brush Saw 75	7121030	267.0	267.0	2158.0	1148.0	748.0