

Applications

Agriculture
Forestry

Landscaping
Road work, Recycling and Cleaning

Main features

The Bobcat® Wood Chipper attachment is ideal for grinding branches, trees and limbs, reducing branch volume from 10 to 1

You can grind branches and trees up to 13 cm in diameter

The discharge chute can be rotated 360°, giving you maximum flexibility of use

Operate the wood chipper from the cabin or using the Bobcat® Remote Attachment Control (RAC) system. This allows the operator to start or stop the loader's engine and chipper rotation when standing beside the attachment

The unit comes with an automatic hydraulic feed, with speed control and a load sensing system for optimum performance and constant flow

Large diameter, high-torque feed roller for increased efficiency and productivity

Variable speed feed drive for adjusting the feed rate with a reversible option in case of plugging

For more work flexibility, dual mounting locations allow material to be fed from the front or right side of the loader


Compatibility

Description	Item number	Compatible with loader
Chipper 5A Non-CE	6719129	A770-B, T450E IIIB, T590E IIIB, T590B iT4, T650E iT4, T650B iT4, T770E IV, T770E T3, T770B T3, T870E IV, T870B T3, S450E IIIA, S450B T2, S510E IIIA, S510B, S530E IIIA, S530B, S550E IIIB, S550B iT4, S570B iT4, S590E IIIB, S590B iT4, S630E iT4, S630B iT4, S650E iT4, S650B iT4, S770E IV, S770E T3, S770B T3, S850E IV, S850E T3, S850B T3, A770E IV, S450 V, S510E V, S530E V, T590E V, T450E V, S66, S76, T66, T76, S510B, S530B, S550E V, S590E V, S630B iT4, S650B iT4
Chipper 8B	7117662	A770-B, T590E IIIB, T590B iT4, T650E iT4, T650B iT4, T770E IV, T770E T3, T770B T3, T870E IV, T870B T3, S530E IIIA, S530B, S550E IIIB, S550B iT4, S570B iT4, S590E IIIB, S590B iT4, S630E iT4, S630B iT4, S650E iT4, S650B iT4, S770E IV, S770E T3, S770B T3, S850E IV, S850E T3, S850B T3, A770E IV, S530E V, T590E V, S66, S76, T66, T76, S530B, S630B iT4, S650B iT4

Characteristics and performance

Description	Item number	Feeder opening (mm)	Continuous chipping size (mm)	Feed table height (mm)	Blades	Flow range (l/min) (L/min)	Discharge chute
Chipper 5A Non-CE	6719129	125.0	75.0	600.0	4 reversible stool steel blades	64.0-98.0	Rotates 360°
Chipper 8B	7117662	235.0	127.0	645.0	4 reversible tool steel blades	98.0-151.0	Rotates 360°

Weights and dimensions



Description	Item number	Operating weight (kg)	Shipping weight (kg)	Overall length (A) (mm)	Overall width (B) (mm)	Overall height (C) (mm)
Chipper 5A Non-CE	6719129	520.0	520.0	-	-	-
Chipper 8B	7117662	753.0	753.0	2594.0	1549.0	2369.0