

### Machine Rating

Rated operating capacity (ISO 14397-1)	810 kg
Tipping load (ISO 14397-1)	1619 kg
Pump capacity	64.70 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range - option)	17.3 km/h
Max. travel speed (low range)	11.8 km/h

### Engine

Make / Model	Kubota / V2203-M-DI-E2B-BC-3
Fuel	Diesel
Cooling	Liquid
Power (SAE J1995) at 2800 RPM:	36.4 kW
Torque (SAE J 1995) at 1700 RPM:	150.0 Nm
Number of cylinders	4
Displacement	2196 cm <sup>3</sup>
Fuel tank	93.70 L

### Weights

Operating weight	2686 kg
Shipping weight	2343 kg

### Controls

Vehicle steering	Direction and speed controlled by two hand levers or optional Advanced Control System (ACS), Advanced Hand Controls (AHC) or Selectable Joystick Controls (SJC)
Loader hydraulics tilt and lift	Separate foot pedals or optional Advanced Control System (ACS), Advanced Hand Controls (AHC) or Selectable Joystick Controls (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

### Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

### Standard Features


Cushion suspension seat	Lift arm support
Automatically activated glow plugs	Noise reduction kit
Auxiliary hydraulics: variable flow/maximum flow	Work lights, front and rear
Bob-Tach™ frame	Parking brake
Bobcat Interlock Control System (BICS)	Seat belt
Deluxe operator cab with windows <sup>1</sup>	Seat bar
Electrically activated proportional front auxiliary hydraulics	Spark arrestor muffler
Engine/hydraulics system shutdown	10 x 16.5, 10-ply, Heavy duty tyres
Hydraulic bucket positioning (including ON/OFF switch)	CE certification
Instrumentation	Warranty: 12 months or 2000 hours (whichever occurs first)

1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

### Options

Deluxe instrument panel	Selectable Joystick Controls (SJC)
Power Bob-Tach™	Two speed
Cab enclosure with heating	Air ride seat with 2 point seat belt
10 x 16.5, 10-ply, Heavy duty tyres, offset rims	Back-up alarm
10 x 16.5, 10-ply, Severe duty tyres	Beacon
12 x 16.5, 12-ply, Severe duty tyres, poly filled	Engine block heater
12 x 16.5, Solid flex tyres	Fire extinguisher
31 x 12-16.5, 10-ply, Superflotation tyres	Radio
Advanced Control System (ACS)	Road kit
Advanced Hand Controls (AHC)	Strobe

### Dimensions



(A)	3787.0 mm	(J)	2908.0 mm
(B)	1972.0 mm	(K)	467.0 mm
(C)	24.2°	(L)	42.0°
(D)	185.0 mm	(M)	97.0°
(E)	1082.0 mm	(N)	1727.0 mm
(F)	2657.0 mm	(O)	2032.0 mm
(G)	3378.0 mm	(P)	1374.0 mm
(H)	30.0°	(Q)	1643.0 mm
(I)	2205.0 mm		

### Attachments

Angle Brooms	Mixing Buckets
Auger Accessories	Mowers
Augers	Pallet Fork Accessories
Backhoes	Pallet Forks, Hydraulic
Bale Forks	Root Grapples
Box Blades	Scarifiers
Breaker Accessories	Scrapers
Breakers	Skeleton Buckets
Brushcat™ Rotary Cutters	Snow & Light Material Buckets
Brush Saws	Snow Blades
Combination Buckets	Snow Pushers
Concrete Mixers	Snow V-Blades
Construction / Industrial Buckets	Sod Layers
Diggers	Soil Conditioners
Dozer Blades	Spreaders
Drop Hammers	Steel Tracks
Dumping Hoppers	Stump Grinders
Fertilizer and Grain Buckets	Sweepers
Flail Cutters	Tillers
General Purpose (GP)	Tilt-Tatch
Bucket	Tree Transplanters
Graders	Trench Compactors
Grapples, Industrial	Utility Forks
Landplanes	Vibratory Rollers
Landscape Rakes	Whisker Brooms
Laser Equipment	Wood Chippers
Low Profile Buckets	
Miscellaneous	