

Performance

Tipping load (ISO 14397-1)	2079 kg
Rated operating capacity (ISO 14397-1)	1040 kg
Pump capacity	87.10 L/min
Pump capacity (with high flow option)	115.50 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range - option)	19.8 km/h
Max. travel speed (low range)	11.4 km/h

Engine

Make / Model	Kubota / V3307-DI-TE3
Fuel	Diesel
Cooling	Liquid
Power at 2400 RPM	55.4 kW
Torque at 1425 RPM (SAE J1995 Gross)	264.0 Nm
Number of cylinders	4
Displacement	3331 cm ³
Fuel tank	103.30 L

Weights

Operating weight	3496 kg
Shipping weight	3244 kg

Controls

Vehicle steering	Direction and speed controlled by two hand levers
Loader hydraulics tilt and lift	Separate foot pedals, optional Advanced Control System (ACS), Advanced Hand Control (AHC) or Selectable Joystick Control (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---


Standard Features

High-back adjustable suspension seat	Lift arm support
Automatically activated glow plugs	Work lights, front and rear
Bob-Tach™ frame	Parking brake
Bobcat Interlock Control System (BICS)	Seat belt
Deluxe operator cab ¹	Seat bar
Electrically activated proportional front auxiliary hydraulics	12 x 16.5, 12-ply, Heavy duty tyres
Engine/hydraulics system shutdown	Turbo-charger with approved spark arrestor
Manual	Warranty: 24 months or 2000 hours (whichever occurs first)

1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

2 Speed	Advanced Control System (ACS)
High-Flow hydraulics	Advanced Hand Controls (AHC)
Deluxe instrument panel	Selectable Joystick Controls (SJC)
Deluxe pressurized cab with heating	Air ride seat with 2 point seat belt
Air conditioning	Air ride seat with 3 point seat belt
Power Bob-Tach™	Back-up alarm
33 x 15.5-16.5, 12-ply, Superflotation tyres, offset rims	Beacon
12 x 16.5, 12-ply, Heavy duty tyres, offset rims	Fire extinguisher
12 x 16.5, 12-ply, Severe duty tyres	Strobe
12 x 16.5, Solid flex tyres	

Dimensions


(A)	3950.0 mm	(J)	3073.0 mm
(B)	2065.0 mm	(K)	544.0 mm
(C)	25.0°	(L)	42.4°
(D)	207.0 mm	(M)	97.0°
(E)	1150.0 mm	(N)	1880.0 mm
(F)	2754.0 mm	(O)	2119.0 mm
(G)	3474.0 mm	(P)	1507.0 mm
(H)	30.0°	(Q)	1832.0 mm
(I)	2367.0 mm		

Attachments

Angle Brooms	Pallet Fork Accessories
Auger Accessories	Pallet Forks, Hydraulic
Augers	Planer Accessories
Backhoe Accessories	Planers
Backhoes	Root Grapples
Bale Forks	Rotary Grinders
Box Blades	Scarifiers
Breaker Accessories	Scrapers
Breakers	Silt Fence Installers
Brushcat™ Rotary Cutters	Skeleton Buckets
Brush Saws	Snow & Light Material Buckets
Combination Buckets	Snow Blades
Concrete Mixers	Snow Pushers
Concrete Pumps	Snow V-Blades
Construction / Industrial Buckets	Sod Layers
Diggers	Soil Conditioners
Dozer Blades	Spreaders
Drop Hammers	Steel Tracks
Dumping Hoppers	Stump Grinders
Fertilizer and Grain Buckets	Sweepers
Flail Cutters	Tillers
Forestry Cutters	Tilt-Tatch
Graders	Tree Transplanters
Grapples, Industrial	Trench Compactors
Landplanes	Trenchers
Landscape Rakes	Utility Forks
Laser Equipment	Utility Frames
Low Profile Buckets	Vibratory Rollers
Miscellaneous	Wheel Saws
Mixing Buckets	Whisker Brooms
Mowers	Wood Chippers